

RFID HangTag Holder

RFID Solution Accessories



USER ADVANTAGES:

- Enables RFID Tag to be inserted and removed at customer's convenience
- Durable, sunlight resistant
- Customizable upon request
- Enables quick, hands-free access

TagMaster's RFID HangTag Holder can be utilized for applications where it is necessary to quickly identify authorized permit holders and ensure a more efficient enforcement operation. This Tag holder can be used to place a TagMaster RFID Tag into the back pouch, enabling vehicles to gain fast and convenient parking access completely hands-free, and also bridging the gap between parking and building access. This Holder is durable, customizable, and is sunlight resistant so the material will not exhibit color change when exposed to direct sunlight.

SPECIFICATIONS

Technical Information	RFID HangTag Holder
Part No. S1960	
Size	3 1/4in x 5 3/4in
Material	.023in filled Polypropylene
Color	Variable
Density	1.04 G/CC (S.G.)
Flexural Modulus	320 KSPI
Notched Izod Impact	1.3 FPIN
Unnotched Izod Impact	No Break FT-LBS
Gardner Impact	120 IN-LBS
-20 F Gardner Impact	24 IN-LBS
Tensile Strength (2 IN/MIN)	4200 PSI
Elongation	35%
HDT @ 66 PSI	240 F
HDT @ 264 PSI	145 F
Rockwell Hardness	90 R
Mold Shrinkage	1.2
MVTR (Relative PVC=1)	0.3

The information in this document may be subject to change without prior notice.